TECHNICAL DATA SHEET



ACCUCHARGER 15A

Professional charger

The professional device for end users, workshops, parts dealers and commercial users

Fully automatic and voltage-regulated dual-voltage charger Extremely easy to use, self-explanatory



PERFORMANCE

Charging: 7 charging stages with fully automatic IUoU charging curve

Refresh mode: For deeply discharged 12V batteries

16V boost program: For used batteries

Supply mode: To prevent the loss of vehicle data when changing batteries Self-recognizing preselection of the battery voltage: For 12V and 24V

Automatic switchover to charge retention mode

Protection function: Against overcharging, overheating, reverse polarity and short circuit

Self-explanatory device with integrated ventilation

APPLICATION

Home / Workshop

12/24 V:



















TECHNICAL DATA

Type: Banner Accucharger 15A Supply voltage: 220-240 V AC, 50/60 Hz

Battery Voltage: 12 V / 24 V DC

Charging Voltage: 14,4 V & 16 V in the boost program

Charging Current: max. 15 A
Battery capacity: 20 up to 110 Ah

Protection: IPX4

Dimension: 300 x 135 x70 mm

Charging cable: Power cable: 180 cm; Battery cable: 135+55 cm

Weight: 2,2 kg

Ambient Temperature: -20 °C to +40 °C

ITEM NUMBER

1240000115



