



## ACCUCHARGER 25A

### Professional charger

The professional device for end users, workshops, parts dealers and commercial users

Fully automatic and voltage-regulated dual-voltage charger

Extremely easy to use, self-explanatory



### PERFORMANCE

Charging: 7 charging stages with fully automatic IUoU charging curve

Refresh mode: For deeply discharged 12V batteries

16V boost program: For used batteries

Supply mode: To prevent the loss of vehicle data when changing batteries

Self-recognizing preselection of the battery voltage: For 12V and 24V

Automatic switchover to charge retention mode

Protection function: Against overcharging, overheating, reverse polarity and short circuit

Self-explanatory device with integrated ventilation

### APPLICATION

#### Home / Workshop

12/24 V:



### TECHNICAL DATA

Type:	Banner AccuCharger 25A
Supply voltage:	220-240 V AC, 50/60 Hz
Battery Voltage:	12 V / 24 V DC
Charging Voltage:	14,4 V & 16 V in the boost program
Charging Current:	max. 25 A
Battery capacity:	30 up to 240 Ah
Protection:	IPX4
Dimension:	300 x 135 x70 mm
Charging cable:	Power cable: 180 cm; Battery cable: 135+55 cm
Weight:	2,2 kg
Ambient Temperature:	-20 °C to +40 °C

**RECOMMENDED LiFePO4  
ACCUCHARGER**

### ITEM NUMBER

1240000125